

NHG60 Gloss Meter 60 degree with GQC6 Software



HG60 gloss meter features with 60° angle, manufactured according to ISO2813 and GB/T 9754. It is also compatible with international standards of ASTM D523, ASTM D2457. HG268 conforms to JJG696 first class gloss meter working requirement, corresponding with CIE 1931(2°) under CIE C light source.

Hg60 gloss meter is widely used to test glossiness in these industries, such as automobile, paint, ink, stoving varnish, coating, wood products; marble, granite, vitrified polished tile, pottery brick and porcelain; plastic, paper; hardware industries, etc.

Features :

1. 60° angle for semi gloss
2. Concise appearance, feel good
3. Display 5 sets of measurement data, good for comparison
4. Built-in lithium ion rechargeable battery
5. Basic model measurement can meet basic glossiness testing requirements
6. Connect to PC, more extend functions
7. One button for all angles measurement at the same location
8. Comply with international standards
9. Stable performance, easy to read data.

Specifications:

NHG60 60° Precise Gloss Meter	
Model	NHG60
Measure Angle	60° Comply with standard ISO 2813、GB/T 9754、ASTM D 523、ASTM D 2457
Measuring Area (mm)	9X15
Measurement Range	0~1000GU
Division Value	0.1GU
Measurement Range Repeatability Reproducibility	0-10GU 10-100GU 100-1000GU± 0.1GU ± 0.2GU ± 0.2%GU± 0.2GU ± 0.5GU ± 0.5%GU
Measurement Standard	Conform with JJG696 first class gloss meter working requirement
Chromaticity Corresponding	Corresponding with CIE 1931(2°) under CIE C light source
Errors	±1.2 , ± 1.2%
Measuring Time	0.5s
Dimension	L*W*H : 160mm*75mm*90mm
Weight	350g
Language	Chinese/English
Battery	3.7V,3200mAh Li-ion Battery, >10000 times(within 8 hours)
Viewing Screen	TFT 3.5 inch, capacitive touch screen
Interface	USB/RS-232
Data Save	Basic mode: 1000, Statistical Mode: 5000, Continuous mode : 5000
Software	GQC6 Quality Control Software with QC report printing functions and more extended functions.
Operation Temperature	0~40°C (32~104°F)
Storage Temperature	-20~50°C (-4~122°F)
Humidity	<85% relative humidity, no condensation
Standard Accessories	Power Adapter, USB cable, User Manual, CD (Including QC software), Calibration Plate
Optional Accessories	Miniature Printer

Contact us:

4B TESTING EQUIPMENTS PVT LTD

Office - 1003, 10th Floor Tower - 3, RPS 12th Avenue Sector - 27C,

Faridabad - 121003, Haryana

Mobile : 9813744722, 9555159647, 8816865099